

Datasheet

19" FO Splice Box Version 215

- 19" splice box for fixed installations 1 U
- Optionally with two-part front panel including angular adapters
- Depth of chassis including front panel: 215 mm
- Backside cable inlets for screwed cable glands 4 x M 20, angular
- Mountable recessed 25 mm or 50 mm

Advantages

- Shallow and variable installation depth
- Modular exchangeable front panels for variable combinations
- More space for patching at the front side


Version: 23.04.2019



19" FO splice box version 215, with angular adapters



19" FO splice box version 215, with angular adapters, open



19" FO splice box version 215

Dimensions	Mounting width	19"
	Mounting height	1 U
	Depth including front panel	215 mm
Material	Sheet steel, powder coated RAL 7035 (Light gray)	
1 U two-part front panels	6 SC duplex adapters	
	6 LC duplex adapters	
	6, 12 and 18 SC /E-2000® (LSH) adapters	
	6 and 12 ST adapters	
	Blind panel	
	Others on request	
	2 front panels per box in customer-specific combinations	
1 U front panels	12 and 24 ST adapters	
	12 and 24 SC/E-2000® (LSH) adapters	
	12 and 24 SC duplex adapters	
	12 and 24 LC duplex adapters	
	24 E-2000® (LSH) compact adapters	
	Blind panel	
	Others on request	

