

# Datasheet

## DIN (LSA) Adapter

Version: 16.05.2017

<b>Manufacturer</b>	EUROMICRON Werkzeuge GmbH	
<b>Compliance</b>	IEC 61754-3, DIN EN 61754-3	
<b>Fixing</b>	Hybrid version	Central fixing M9 x 0.5 incl. washer and nut
	Standard version	Central fixing M5.5 x 0.5 incl. 2 ring nuts
<b>Temperature range</b>	Operating temperature	-40° C to +85° C
	Storage temperature	-40° C to +90° C
<b>Versions</b>	Simplex / multimode	
	Simplex / singlemode	
	Simplex / singlemode APC	



DIN (LSA) singlemode adapter

### Multimode

<b>Sleeve material</b>	Zirconia, slitted
<b>Housing material</b>	Metal
<b>Mating cycles</b>	2,000
<b>Typical loss</b>	≤ 0.15 dB

### Singlemode

<b>Sleeve material</b>	Zirconia, slitted
<b>Housing material</b>	Metal
<b>Mating cycles</b>	1,000
<b>Typical loss</b>	≤ 0.10 dB



**Singlemode APC**

<b>Sleeve material</b>	Zirconia, slitted
<b>Housing material</b>	Metal
<b>Mating cycles</b>	1,000
<b>Typical loss</b>	≤ 0.10 dB

