

# Datasheet

## FTTH Fiber Termination Box

- Space-saving, non-standardized wall-mounting for FTTH installations
- Suitable for splicing and patching
- Integrated cable guide and snap-lock cover ensure comfortable use and maintenance
- Plastic housing free of halogen
- Good resistance to chemicals and UV radiation
- Operating temperature -45° to +80°C
- Suitable for mounting of different adapter types inside or outside of the enclosure (max. 8 fibers)
- Additional storage position for unused fibers
- Several perforated cable inlets and outlets ensure necessary installation flexibility:
  - 3 cable inlets for max. 12 mm cable diameter, seal inserts for cable diameter 3mm to max. 12mm
  - 1 cable inlets for M12
  - 2 additional cable outlets for max. 30mm (1x oval, 1x round)
- Lockable variation available

Dimensions	Width	150 mm
	Height	250 mm
	Depth	46 mm
Material	Corrosion-free and durable polycarbonate Flammability rating UL94 V-0 Fully RoHS compliant	
Protection class	IP54 (EN 60529) ingress protection IK08 (EN 62262) impact resistance	
Distribution panel	4 LC duplex adapters	
	4 SC / E-2000® (LSH) adapters	
	Others on request	

Version: 27.05.2020



FTTH fiber termination box - closed



FTTH fiber termination box - opened