

# Datasheet

## FTTH Fiber Termination Box

Version: 27.05.2020

- Space-saving, non-standardized wall-mounting for FTTH installations
- Suitable for splicing and patching
- Integrated cable guide and snap-lock cover ensure comfortable use and maintenance
- Plastic housing free of halogen
- Good resistance to chemicals and UV radiation
- Operating temperature -45° to +80 °C
- Suitable for mounting of different adapter types inside or outside of the enclosure (max. 8 fibers)
- Additional storage position for unused fibers
- Several perforated cable inlets and outlets ensure necessary installation flexibility:
  - 3 cable inlets for max. 12 mm cable diameter, seal inserts for cable diameter 3mm to max. 12mm
  - 1 cable inlets for M12
  - 2 additional cable outlets for max. 30mm (1x oval, 1x round)
- Lockable variation available



FTTH fiber termination box - closed



FTTH fiber termination box - opened

|                    |  |        |
|--------------------|--|--------|
| Dimensions         | Width  | 150 mm |
|                    | Height   | 250 mm |
|                    | Depth  | 46 mm  |
| Material           | Corrosion-free and durable polycarbonate<br>Flammability rating UL94 V-0<br>Fully RoHS compliant |        |
| Protection class   | IP54 (EN 60529) ingress protection<br>IK08 (EN 62262) impact resistance                          |        |
| Distribution panel | 4 LC duplex adapters   |        |
|                    | 4 SC / E-2000® (LSH) adapters  |        |
|                    | Others on request  |        |

