


Datasheet

LC Quad Adapter

Version: 16.05.2017

Manufacturer	EUROMICRON Werkzeuge GmbH	
Compliance	IEC 61754-20, DIN EN 61754-20, TIA-604-10-B	
Fixing	Clip mounting or 2-hole flange mounting LC quad adapter fits a SC duplex opening	
Temperature range	Operating temperature	-40 °C to +80 °C
	Storage temperature	-40 °C to +80 °C
Versions	4-fold / multimode	Phosphor bronze sleeve
		Zirconia sleeve
	4-fold / singlemode	Zirconia sleeve
	4-fold / singlemode APC	Zirconia sleeve



LC Quad adapter

Multimode

Sleeve material	Phosphor bronze, slitted
Housing material	Plastic / Beige (OM 1, OM 2)
Mating cycles	1,000
Typical loss	≤ 0.20 dB

Multimode

Sleeve material	Zirconia, slitted
Housing material	Plastic / Aqua (OM 3) Plastic / Heather violet (OM 4)
Mating cycles	1,000
Typical loss	≤ 0.20 dB

Singlemode

Sleeve material	Zirconia, slitted
Housing material	Plastic / Blue
Mating cycles	1,000
Typical loss	≤ 0.20 dB

Singlemode APC

Sleeve material	Zirconia, slitted
Housing material	Plastic / Green
Mating cycles	1,000
Typical loss	≤ 0.20 dB

